KHULNA SHIPYARD LIMITED

BANGLADESH NAVY, KHULNA

PHONE: 02-4411-0990, FAX: 880-41-720404

E-mail: contact@khulnashipyard.com, oiccomf.ksy@gmail.com

BABE (F) - 314/2020-2021/

27 January 2021

Dear Sir

INVITATION FOR QUOTATION OF 37° FLARE INNER SLEEVE FOR FLARE TYPE HYDRAULIC COUPLING

- 1. Khulna Shipyard Limited will procure 37° Flare Inner Sleeve for Flare Type Hydraulic Coupling as per attached specification 01 (One) Page and Picture 02 (Two) Pages.
- 2. a) Please send your offer CPT/CFR at Dhaka Airport/ Chattogram Port within 04/02/2021 (1500 Hours) by e-mail or closed envelop.
 - b) Insurance will be covered by this organization.
 - c) Payment: Payment will be made through L/C. 80% of the total contract value will be paid against shipping documents and rest 20% will be paid after receiving the material at KSY and satisfactory acceptance.
 - d) Shipment: 20 days from the opening date of L/C.

OR,

Submission of quotation as local supply terms:

- a) Please send your offer as a local supply items. Offer should include supply of materials at KSY site including custom duty, local vat & tax etc.
- b) Payment: 100% payment will be made after receiving the material at KSY and satisfactory acceptance after deducting of VAT and TAX.
- c) Items to be delivered within 45 days from the date of Purchase Order at KSY site.
- 3. **1%** (one) Bid Bond/Earnest Money of the total quoted CPT/CFR value must be submit with offer. Bid Bond may be Pay Order / Bank Guarantee in favour of Khulna Shipyard Limited, Khulna.
- 4. 10% Performance Guarantee (PG) is to be submitted before Purchase Order. This PG will release after receiving the material and satisfactory acceptance by KSY.
- 5. Offer Validity: 45 Days from Tender Opening Date.

Yours sincerely

SK. SHAH MOSHIUR RAHMAN Manager Commercial

For Managing Director

37° FLARE INNER SLEEVE FOR FLARE TYPE HYDRAULIC COUPLING

SL No	Description	Code No	Quanti
			ty
1	37º Flare inner sleeve for flare type hydraulic coupling,	28B/New	15 Pc
	Size (Tube/ pipe OD) : 12 mm,		
	Sleeve size (ID X OD ₁ X OD ₂ X Overall length X Collar length at flare side):		
	(12.2 X 16.2 X 13.5 X 13 X 5.5) mm,		
	Operating pressure: 330 bar, Material: High strength steel,		
	Size, shape and material : As per sample.	207 (11	155
2	37º Flare inner sleeve for flare type hydraulic coupling,	28B/ New	15 Pc
	Size (Tube/ pipe OD): 16 mm,		
	Sleeve size (ID X OD ₁ X OD ₂ X Overall length X Collar length at flare side): $(16.2 \times 22 \times 19.5 \times 17.4 \times 6.6)$		
	(16.2 X 22 X 18.5 X 17 X 6.6) mm, Operating pressure: 330 bar, Material: High strength steel,		
	Size, shape and material: As per sample.		
3	37º Flare inner sleeve for flare type hydraulic coupling,	28B/ New	15 Pc
3	Size (Tube/ pipe OD) : 20 mm,	ZOD/ NCW	1310
	Sleeve size (ID X OD ₁ X OD ₂ X Overall length X Collar length at flare side):		
	(20.2 X 27.7 X 24.2 X 17.6 X 7.5) mm,		
	Operating pressure: 330 bar, Material: High strength steel,		
	Size, shape and material : As per sample.		
4	37º Flare inner sleeve for flare type hydraulic coupling,	28B/New	10 Pc
	Size (Tube/ pipe OD) : 25 mm,		
	Sleeve size (ID X OD ₁ X OD ₂ X Overall length X Collar length at flare side):		
	(25.2 X 32.75 X 28.45 X 20 X 8) mm,		
	Operating pressure: 330 bar, Material: High strength steel,		
	Size, shape and material : As per sample.		
5	37º Flare inner sleeve for flare type hydraulic coupling,	28B/ New	10 Pc
	Size (Tube/ pipe OD): 30 mm,		
	Sleeve size (ID X OD_1 X OD_2 X Overall length X Collar length at flare side):		
	(30.2 X 39 X 34 X 21.5 X 8) mm,		
	Operating pressure: 330 bar, Material: High strength steel,		
	Size, shape and material : As per sample.		
6	37º Flare inner sleeve for flare type hydraulic coupling,	28B/ New	10 Pc
	Size (Tube/ pipe OD): 38 mm,		
	Sleeve size (ID X OD ₁ X OD ₂ X Overall length X Collar length at flare side): $(39.3 \times 49.4 \times 42 \times 36.6 \times 10)$		
	(38.2 X 48.4 X 42 X 26.6 X 10) mm,		
	Operating pressure: 330 bar, Material: High strength steel, Size, shape and material: As per sample.		
	Size, shape and material. As per sample.		





