



KHULNA SHIPYARD LIMITED

BANGLADESH NAVY, KHULNA

PHONE : 02-4411-0990, FAX : 880-41-720404

E-mail : dgml.ksy@gmail.com; oiocomf.ksy@gmail.com

BABE (F) – 123/2023-2024/

06 April 2024

Dear Sir

INVITATION FOR QUOTATION OF JOHNSON CUTLESS NON-METALLIC SLEEVE BEARING

1. Khulna Shipyard Limited will procure Johnson Cutless non-metallic sleeve bearing as per attach specification & picture (01 Pages), following terms & condition:

Description	Qty
Johnson Cutless non-metallic sleeve bearing	04 Pcs

2. Please send your offer CPT Dhaka Airport basis within 16 May 2024 by e-mail.
- Insurance will be covered by this organization.
 - Payment: Payment will be made through irrevocable letter of credit (LC). 80% of the total contract value will be paid against shipping documents and rest 20% will be paid after receiving the material at KSY and satisfactory acceptance.
 - Shipment: 15 days from the opening date of L/C.
3. 5% Performance Guarantee (by Pay Order) is to be submitted before Purchase Order.
4. Warranty: 12 (Twelve) months after acceptance by KSY. During warranty period the quality and quantity will have to replace the defective materials and replenish the short supplied quantity free of charge on demand by KSY.
5. Offer Validity: 45 Days.

Yours sincerely

SK. SHAH MOSHIUR RAHMAN
Manager Admin
For Managing Director

JOHNSON CUTLESS NON-METALLIC SLEEVE BEARING

Country Origin	USA
Country Manufacture	DURAMAX MARINE LLC
Manufacturing Year	2024
Brand	Duramax Marine
Size	Shaft diameter:88.90 mm, Bush Outside Diameter:108.35 mm, Bush Length:355.60 mm, Shell Thick:3.18mm
Weight	To be mentioned.
Installation	It will be suited for installations wherever corrosion or electrolysis is a problem. Proper installation guide line is to be supplied.
Bush/ Bearing Housing Bore	108.30mm (for selecting the bush outside diameter)
Shaft Dia Meter	88.90 mm
Warranty	01 (One) Year after satisfactory test-trail.
Part Number	To be mentioned.
Code	To be mentioned.
Lubrication	Water lubricated. Number of water grooves are to be mentioned as per standard.
Type Approval Certificate	Full type approval from any international classification society to be supplied.
Composition	The specially compounded Nitrile Rubber is securely bonded to the shell of a dense structure of engineered reinforced thermoset plastic with maintaining all tolerances.

